

COMPLETE LISTING OF CLAIMS**IN ASCENDING ORDER WITH STATUS INDICATOR**

1. (Currently Amended) A multi-domain liquid crystal display device comprising:
- first and second substrates opposing each other between a liquid crystal layer;
 - a plurality of gate lines and data lines on the first substrate lengthwise and crosswise, to define ~~[[a]]~~ at least two pixel region regions;
 - a common auxiliary electrode on a layer equal to the gate lines to surround each of the pixel region regions;
 - a gate insulating film on the first substrate;
 - a passivation film on the gate insulating film including the first substrate;
 - a pixel electrode in each of the pixel region regions, wherein at least one of the pixel electrode regions is divided into a plurality of domains;
 - a light-shielding layer on the second substrate;
 - a color filter layer on the light-shielding layer;
 - a common electrode on the color filter layer;
 - ~~a plurality of~~ at least one electric field distortion dielectric ~~structures~~ structure in each of the plurality of domains at least two pixel regions, wherein the dielectric ~~structure~~ structures in ~~the neighboring domains~~ pixel regions have ~~unequal shapes~~ different configurations; and
 - an alignment film on at least one of the first and second substrates.
2. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the pixel electrode overlaps the common auxiliary electrode.

3. (Original) The multi-domain liquid crystal display device as claimed in claim 2, where the light-shielding layers overlaps the common auxiliary electrode.

FI
Copy

4. (Currently Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;
a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise,
to define [[a]] at least two pixel region regions;

a common auxiliary electrode on a layer equal to the gate lines to surround each of the pixel region regions;

a gate insulating film on the first substrate;

a passivation film on the gate insulating film including the first substrate;

a pixel electrode in each of the pixel region regions, wherein at least one of the pixel electrode regions is divided into a plurality of domains; the pixel electrode not overlapping the common auxiliary electrode;

a light-shielding layer on the second substrate;

a color filter layer on the light-shielding layer;

a common electrode on the color filter layer;

a plurality of at least one electric field distortion dielectric structures structure in each of the plurality of domains at least two pixel regions, wherein the dielectric ~~structure~~ structures in the neighboring ~~domains pixel regions~~ have unequal shapes different configurations; and

an alignment film on at least one of the first and second substrates.

5. (Original) The multi-domain liquid crystal display device as claimed in claim 4, wherein the light-shielding layer overlaps the pixel electrode.

6. (Original) The multi-domain liquid crystal display device as claimed in claim 4, wherein the gate insulating film and the passivation film are formed in a region except the common auxiliary electrode.

7. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the common auxiliary electrode is electrically connected with the common electrode.

8. (Previously Presented) The multi-domain liquid crystal display device as claimed in claim 1, further comprising a thin film transistor formed in a crossing point of the gate lines and the data lines.

9. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the electric field dielectric structures are formed on the pixel electrode.

10. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the electric field dielectric structures are formed on the common electrode.

11. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the electric field dielectric structures are formed on the color filter layer.

12. (Currently Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;

E/
Cm 4

a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise, to define [[a]] at least two pixel region regions;

a common auxiliary electrode on a layer equal to the gate lines to surround each of the pixel region regions;

a gate insulating film on the first substrate;

a passivation film on the gate insulating film including the first substrate, ~~the pixel electrode having an electric field induction window therein;~~

a pixel electrode in each of the pixel region regions, wherein at least one of the pixel electrode regions is divided into a plurality of domains, the pixel electrode having an electric field induction window therein;

a light-shielding layer on the second substrate;

a color filter layer on the light-shielding layer;

a common electrode on the color filter layer;

~~a plurality of at least one electric field distortion dielectric structures structure in each of the plurality of domains at least two pixel regions,~~ wherein the dielectric ~~structure structures~~ in the neighboring domains pixel regions have unequal shapes different configurations; and

an alignment film on at least one of the first and second substrates.

13. (Currently Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;
a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise, to define [[a]] at least two pixel region regions;

a common auxiliary electrode on a layer equal to the gate lines to surround each of the pixel region regions;

El
Cont'd

a gate insulating film on the first substrate;
a passivation film on the gate insulating film including the first substrate, the passivation film having an electric field induction window therein;
a pixel electrode in each of the pixel region regions, wherein at least one of the pixel electrode regions is divided into a plurality of domains;
a light-shielding layer on the second substrate;
a color filter layer on the light-shielding layer;
a common electrode on the color filter layer;
a plurality of at least one electric field distortion dielectric ~~structures~~ structure in each of the plurality of domains at least two pixel regions, wherein the dielectric ~~structure~~ structures in the neighboring ~~domains~~ pixel regions have unequal shapes different configurations; and
an alignment film on at least one of the first and second substrates.

14. (Currently Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;
a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise, to define [[a]] at least two pixel region regions;
a common auxiliary electrode on a layer equal to the gate lines to surround each of the pixel region regions;
a gate insulating film on the first substrate, the gate insulating film having an electric field induction window therein;
a passivation film on the gate insulating film including the first substrate;
a pixel electrode in each of the pixel region regions, wherein at least one of the pixel electrode regions is divided into a plurality of domains;

E/ Com'd

a light-shielding layer on the second substrate;
a color filter layer on the light-shielding layer;
a common electrode on the color filter layer;
~~a plurality of at least one~~ electric field distortion dielectric ~~structures~~ structure in each of
the ~~plurality of domains~~ at least two pixel regions, wherein the dielectric ~~structure~~ structures in
the neighboring ~~domains~~ pixel regions have ~~unequal shapes~~ different configurations; and
an alignment film on at least one of the first and second substrates.

15. (Currently Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;
a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise,
to define ~~[[a]]~~ at least two pixel region region;

a common auxiliary electrode on a layer equal to the gate lines to surround each of the
pixel ~~region~~ regions;

a gate insulating film on the first substrate;
a passivation film on the gate insulating film including the first substrate;
a pixel electrode in each of the pixel ~~region~~ regions, wherein at least one of the pixel
~~electrode~~ regions is divided into a plurality of domains;

a light-shielding layer on the second substrate;
a color filter layer on the light-shielding layer;
a common electrode on the color filter layer, the common electrode having an electric
field induction window therein;

~~a plurality of at least one~~ electric field distortion dielectric ~~structures~~ structure in each of
the ~~plurality of domains~~ at least two pixel regions, wherein the dielectric ~~structure~~ structures in

~~the neighboring domains pixel regions have unequal shapes different configurations; and~~
~~an alignment film on at least one of the first and second substrates.~~

E1
Cont'd

16. (Currently Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;
a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise,
to define ~~[[a]] at least two pixel region regions;~~

~~a common auxiliary electrode on a layer equal to the gate lines to surround each of the~~
~~pixel region regions;~~

~~a gate insulating film on the first substrate;~~

~~a passivation film on the gate insulating film including the first substrate;~~

~~a pixel electrode in each of the pixel region regions, wherein at least one of the pixel~~
~~electrode regions is divided into a plurality of domains;~~

~~a light-shielding layer on the second substrate;~~

~~a color filter layer on the light-shielding layer, the color filter layer having an electric~~
~~field induction window therein;~~

~~a common electrode on the color filter layer;~~

~~a plurality of at least one electric field distortion dielectric structures structure in each of~~
~~the plurality of domains at least two pixel regions, wherein the dielectric structure structures in~~
~~the neighboring domains pixel regions have unequal shapes different configurations; and~~
~~an alignment film on at least one of the first and second substrates.~~

17. (canceled)

E1
Cont'd

18. (Currently Amended) A multi-domain liquid crystal display device comprising:

- first and second substrates opposing each other between a liquid crystal layer;
- a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise, to define [[a]] at least two pixel region regions;
- a common auxiliary electrode on a layer equal to the gate lines to surround each of the pixel region regions;
- a gate insulating film on the first substrate;
- a passivation film on the gate insulating film including the first substrate;
- a pixel electrode in each of the pixel region regions, wherein at least one of the pixel electrode regions is divided into a plurality of domains;
- a light-shielding layer on the second substrate;
- a color filter layer on the light-shielding layer;
- an over coat layer on the color filter layer, the over coat layer having an electric field induction window therein;
- a common electrode on the over coat layer;
- ~~a plurality of~~ at least one electric field distortion dielectric ~~structures~~ structure in each of the plurality of domains at least two pixel regions, wherein the dielectric ~~structure~~ structures in the neighboring domains pixel regions have unequal shapes different configurations; and
- an alignment film on at least one of the first and second substrates.

19. (Currently Amended) The multi-domain liquid crystal display device as claimed in claim 1, wherein the passivation film ~~emprises~~ comprises a material selected from one group consisting of BCB, acrylic resin and polyimide

20. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the passivation film comprises a material selected from one group consisting of SiN_x , and SiO_x .

21. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the common auxiliary electrode comprises a material selected from one group consisting of ITO, Al, Mo, Cr, Ta, Ti and Al alloy.

22. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the pixel electrode comprises a material selected from one group consisting of ITO, Al and Cr.

23. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the common electrode comprises ITO.

24. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the dielectric structure has a dielectric constant smaller than that of the liquid crystal layer.

25. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the dielectric structure comprises a photosensitive material.

26. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the dielectric structure comprises a material selected from one group consisting of

photoacrylate and BCB.

E1
Cm'd

27. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the pixel region is divided into at least two regions so that the liquid crystal molecules of the liquid crystal layer have different driving characteristics on each region.

28. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the alignment film is divided into at least two regions so that liquid crystal molecules of the liquid crystal layer have different alignment characteristics on each region.

29. (Original) The multi-domain liquid crystal display device as claimed in claim 28, wherein at least one region of the alignment film is aligned.

30. (Currently Amended) The multi-domain liquid crystal display device as claimed in claim 28, wherein at least one of the region two regions of the alignment film is not aligned.

31. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the liquid crystal constituting the liquid crystal layer has a positive dielectric anisotropy or a negative dielectric anisotropy.

32. (Original) The multi-domain liquid crystal display device as claimed in claim 1, further comprising a negative uniaxial film on at least one of the first substrate and the second substrate.

33. (Original) The multi-domain liquid crystal display device as claimed in claim 1, further comprising a negative biaxial film on at least one of the first substrate and the second substrate.

E1
Cm'd

34. (Original) The multi-domain liquid crystal display device as claimed in claim 1, wherein the liquid crystal layer includes a chiral dopant.

35. (Currently Amended) A multi-domain liquid crystal display device comprising:
a data line to apply a data signal;
a pixel electrode for driving a liquid crystal;
a gate line crossed to the data line, to define a pixel region;
a common auxiliary electrode formed to surround the pixel region; and
a plurality of electric field distortion structures formed in different ~~forms~~ configurations
within neighboring ~~pixels~~ pixel regions.

36. (Original) The multi-domain liquid crystal display device as claimed in claim 35, wherein the common auxiliary electrode is formed on a layer same as the gate line.

37. (Currently Amended) A multi-domain liquid crystal display device comprising:
a data line to apply a data signal;
a pixel electrode for driving a liquid crystal, wherein the pixel electrode is divided into a plurality of domains, the pixel electrode having an electric field induction window therein;
a gate line crossed to the data line, to define a pixel region;
a common auxiliary electrode formed to surround the pixel region; and

*E1
Correct*

a plurality of electric field distortion dielectric structures in the plurality of domains,
wherein the dielectric ~~structure~~ structures in ~~the~~ neighboring ~~domains~~ pixel regions have ~~unequal~~
shapes different configurations.